



# Ezyflow™ Water Sampling Pump

## INTRODUCTION

Easy to load pump head with quick connect carrier. The Ezyflow™ EZ-65-000 is designed for low flow sampling.

## INCLUDES

Ezyflow™ easy to load pump head and AC adapter.

## KEY FEATURES

- Small compact design
- Robust and easy to carry
- Illuminated "ON/OFF" indicator
- Speed control from low to high speeds
- Reversible flow and prime/purge function
- Suitable for various liquids
- Samples from depths of up to 7.9 m (26 ft)
- Supporting various tube material for transferring different liquids
- IP54-rated control panel protects against inclement weather and splashing water
- Easy top plate charging station
- Rechargeable battery - ideal for field applications



SKU: 24419

## SPECIFICATIONS

- Model: Ezyflow™ Water Sampling Pump
- Type: Peristaltic with easy to load system
- Flow Range: 0 - 1740 ml/min.
- Max. Speed: 600 RPM
- Variable Speed: Manual control knob
- Pump Head: Quick connect Ezyflow™
- Motor: 12V DC
- Power: 115/230V AC
- Tubing Sizes: 15 & 24
- Drive IP Rating / Weather Proof: IP54
- Dimensions: 17.5" L x 8" W x 8.5" H

## ACCESSORIES

#5004.47 - (1) #15 X 50' Silicone Tubing, (.19" ID X .39" OD)

#5004.38 - (1) .17 ID X 1/4" OD X 100' Poly Tubing

## TECHNICAL PARAMETERS

<u>Model</u>	<u>Pump Head</u>	<u>Motor</u>	<u>Tube</u>	<u>Flow Range</u>	<u>Max. Speed</u>
EZ-65000	Ezyflow™	12V DC	15 or 24	0 - 1740 ml/min.	600 RPM

Agricultural  
Geotechnical  
Environmental  
Groundwater

105 Harrison St.  
American Falls, ID 83211

Toll Free: 800-635-7330  
Office: 208-226-2017

ams@ams-samplers.com

[www.facebook.com/amssampling](https://www.facebook.com/amssampling)

[www.instagram.com/amsinc/](https://www.instagram.com/amsinc/)

[www.linkedin.com/company/ams-inc/](https://www.linkedin.com/company/ams-inc/)

[www.ams-samplers.com](http://www.ams-samplers.com)

